

V03586

Premium Color Hand Film, Black

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Blown
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Black
Film Width (inches)	18"
Length (feet)	1500'
Net Weight / Roll (lb, nominal)	6.8 lb
Roll Diameter (O.D.)	5.5"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6900
Ultimate Tensile TD	4900
Elongation MD	450
Elongation TD	600
Tear Resistance MD	140
Tear Resistance TD	700
Puncture Resistance	25 gms
Ultimate Prestrech	275%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03587

Premium Color Hand Film, Blue

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Blown
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Blue
Film Width (inches)	18"
Length (feet)	1500'
Net Weight / Roll (lb, nominal)	6.8 lb
Roll Diameter (O.D.)	5.5"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6900
Ultimate Tensile TD	4900
Elongation MD	450
Elongation TD	600
Tear Resistance MD	140
Tear Resistance TD	700
Puncture Resistance	25 gms
Ultimate Prestrech	275%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03588

Premium Color Hand Film, Green

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Blown
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Green
Film Width (inches)	18"
Length (feet)	1500'
Net Weight / Roll (lb, nominal)	6.8 lb
Roll Diameter (O.D.)	5.5"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6900
Ultimate Tensile TD	4900
Elongation MD	450
Elongation TD	600
Tear Resistance MD	140
Tear Resistance TD	700
Puncture Resistance	25 gms
Ultimate Prestrech	275%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03669

Premium Color Hand Film, Red

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Blown
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Red
Film Width (inches)	18"
Length (feet)	1500'
Net Weight / Roll (lb, nominal)	6.8 lb
Roll Diameter (O.D.)	5.5"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6900
Ultimate Tensile TD	4900
Elongation MD	450
Elongation TD	600
Tear Resistance MD	140
Tear Resistance TD	700
Puncture Resistance	25 gms
Ultimate Prestrech	275%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03670

Premium Color Hand Film, Yellow

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Blown
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Yellow
Film Width (inches)	18"
Length (feet)	1500'
Net Weight / Roll (lb, nominal)	6.8 lb
Roll Diameter (O.D.)	5.5"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6900
Ultimate Tensile TD	4900
Elongation MD	450
Elongation TD	600
Tear Resistance MD	140
Tear Resistance TD	700
Puncture Resistance	25 gms
Ultimate Prestrech	275%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03671

Premium Color Hand Film, White

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Blown
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	White
Film Width (inches)	18"
Length (feet)	1500'
Net Weight / Roll (lb, nominal)	6.8 lb
Roll Diameter (O.D.)	5.5"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6900
Ultimate Tensile TD	4900
Elongation MD	450
Elongation TD	600
Tear Resistance MD	140
Tear Resistance TD	700
Puncture Resistance	25 gms
Ultimate Prestrech	275%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03681

Premium Color Hand Film, White

20.3 Micron / 80 Gauge / 0.80 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Blown
Thickness (nominal)	20.3 Micron / 80 Gauge / 0.80 Mil
Color	White
Film Width (inches)	18"
Length (feet)	1500'
Net Weight / Roll (lb, nominal)	8.64 lb
Roll Diameter (O.D.)	5.5–6"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6200
Ultimate Tensile TD	4800
Elongation MD	500
Elongation TD	670
Tear Resistance MD	90 g
Tear Resistance TD	350
Puncture Resistance	61 gms
Ultimate Prestrech	275%
Cling	250 g

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03673

Premium Color Machine Film, Black

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Black
Film Width (inches)	20"
Length (feet)	5000'
Net Weight / Roll (lb, nominal)	25.2 lb
Roll Diameter (O.D.)	8.25–9.25"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	11755
Ultimate Tensile TD	4697
Elongation MD	350
Elongation TD	872
Tear Resistance MD	73
Tear Resistance TD	665
Puncture Resistance	51 gms
Ultimate Prestrech	250%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03674

Premium Color Machine Film, Blue

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Blue
Film Width (inches)	20"
Length (feet)	5000'
Net Weight / Roll (lb, nominal)	25.2 lb
Roll Diameter (O.D.)	8.25–9.25"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	11755
Ultimate Tensile TD	4697
Elongation MD	350
Elongation TD	872
Tear Resistance MD	73
Tear Resistance TD	665
Puncture Resistance	51 gms
Ultimate Prestrech	250%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03675

Premium Color Machine Film, Green

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Green
Film Width (inches)	20"
Length (feet)	5000'
Net Weight / Roll (lb, nominal)	25.2 lb
Roll Diameter (O.D.)	8.25–9.25"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	11755
Ultimate Tensile TD	4697
Elongation MD	350
Elongation TD	872
Tear Resistance MD	73
Tear Resistance TD	665
Puncture Resistance	51 gms
Ultimate Prestrech	250%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03676

Premium Color Machine Film, Red

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Red
Film Width (inches)	20"
Length (feet)	5000'
Net Weight / Roll (lb, nominal)	25.2 lb
Roll Diameter (O.D.)	8.25–9.25"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	11755
Ultimate Tensile TD	4697
Elongation MD	350
Elongation TD	872
Tear Resistance MD	73
Tear Resistance TD	665
Puncture Resistance	51 gms
Ultimate Prestrech	250%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03677

Premium Color Machine Film, Yellow

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Yellow
Film Width (inches)	20"
Length (feet)	5000'
Net Weight / Roll (lb, nominal)	25.2 lb
Roll Diameter (O.D.)	8.25–9.25"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	11755
Ultimate Tensile TD	4697
Elongation MD	350
Elongation TD	872
Tear Resistance MD	73
Tear Resistance TD	665
Puncture Resistance	51 gms
Ultimate Prestrech	250%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03678

Premium Color Machine Film, White

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	White
Film Width (inches)	20"
Length (feet)	5000'
Net Weight / Roll (lb, nominal)	25.2 lb
Roll Diameter (O.D.)	8.25–9.25"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	11755
Ultimate Tensile TD	4697
Elongation MD	350
Elongation TD	872
Tear Resistance MD	73
Tear Resistance TD	665
Puncture Resistance	51 gms
Ultimate Prestrech	250%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS

V03680

Premium Color Machine Film, Blue

20.3 Micron / 80 Gauge / 0.80 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Blown
Thickness (nominal)	20.3 Micron / 80 Gauge / 0.80 Mil
Color	Blue
Film Width (inches)	20"
Length (feet)	5000'
Net Weight / Roll (lb, nominal)	32 lb
Roll Diameter (O.D.)	9"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6800
Ultimate Tensile TD	5600
Elongation MD	670
Elongation TD	825
Tear Resistance MD	175
Tear Resistance TD	618
Puncture Resistance	180 gms
Ultimate Prestrech	325%
Cling	350 g

TUFFlex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2018 TUFFlex and the TUFFlex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

09/18
PKTFSpStretchTDS