

V03685

Premium Plus Banding Film

11.9 Micron / 47 Gauge / 0.47 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	11.9 Micron / 47 Gauge / 0.47 Mil
Color	Clear
Film Width (inches)	5"
Length (feet)	1000'
Net Weight / Roll (lb, nominal)	0.94 lb
Roll Diameter (O.D.)	4.25"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	13759
Ultimate Tensile TD	5117
Elongation MD	264
Elongation TD	885
Tear Resistance MD	46
Tear Resistance TD	468
Puncture Resistance	46 gms
Ultimate Prestrech	220–250%
Cling	> / = 60

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2019 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

8/19
PKTFSpStretchTDS

V03579

Premium Plus Banding Film

14 Micron / 55 Gauge / 0.55 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	14 Micron / 55 Gauge / 0.55 Mil
Color	Clear
Film Width (inches)	3"
Length (feet)	1000'
Net Weight / Roll (lb, nominal)	0.659 lb
Roll Diameter (O.D.)	4.5"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6559
Ultimate Tensile TD	2843
Elongation MD	438
Elongation TD	688
Tear Resistance MD	172
Tear Resistance TD	321
Puncture Resistance	90 gms
Ultimate Prestrech	220%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2019 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

8/19
PKTFSpStretchTDS

V03581

Premium Plus Banding Film

14 Micron / 55 Gauge / 0.55 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	14 Micron / 55 Gauge / 0.55 Mil
Color	Clear
Film Width (inches)	5"
Length (feet)	1000'
Net Weight / Roll (lb, nominal)	1.1 lb
Roll Diameter (O.D.)	4.5"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6559
Ultimate Tensile TD	2843
Elongation MD	438
Elongation TD	688
Tear Resistance MD	172
Tear Resistance TD	321
Puncture Resistance	90 gms
Ultimate Prestrech	220%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2019 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

8/19
PKTFSpStretchTDS

V03580

Premium Plus Banding Film

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Clear
Film Width (inches)	3"
Length (feet)	1000'
Net Weight / Roll (lb, nominal)	0.755 lb
Roll Diameter (O.D.)	4.5–4.75"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6048
Ultimate Tensile TD	4570
Elongation MD	597
Elongation TD	728
Tear Resistance MD	269
Tear Resistance TD	325
Puncture Resistance	51 gms
Ultimate Prestrech	250%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2019 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

8/19
PKTFSpStretchTDS

V03582

Premium Plus Banding Film

16 Micron / 63 Gauge / 0.63 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	16 Micron / 63 Gauge / 0.63 Mil
Color	Clear
Film Width (inches)	5"
Length (feet)	1000'
Net Weight / Roll (lb, nominal)	1.26 lb
Roll Diameter (O.D.)	4.5–4.75"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	11755
Ultimate Tensile TD	4697
Elongation MD	350
Elongation TD	872
Tear Resistance MD	73
Tear Resistance TD	665
Puncture Resistance	51 gms
Ultimate Prestrech	250%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2019 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

8/19
PKTFSpStretchTDS

V04229

Premium Plus Banding Film

20.3 Micron / 80 Gauge / 0.80 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	20.3 Micron / 80 Gauge / 80 Mil
Color	Clear
Film Width (inches)	3"
Length (feet)	1000'
Net Weight / Roll (lb, nominal)	0.96 lb
Roll Diameter (O.D.)	5"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6756
Ultimate Tensile TD	3338
Elongation MD	537
Elongation TD	781
Tear Resistance MD	250
Tear Resistance TD	450
Puncture Resistance	128 gms
Ultimate Prestrech	220–250%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2019 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

8/19
PKTFSpStretchTDS

V03583

Premium Plus Banding Film

20.3 Micron / 80 Gauge / 0.80 Mil

Not intended as limiting specifications.

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	20.3 Micron / 80 Gauge / 0.80 Mil
Color	Clear
Film Width (inches)	5"
Length (feet)	1000'
Net Weight / Roll (lb, nominal)	1.6 lb
Roll Diameter (O.D.)	5"
Core I.D.	3"

TESTS	VALUES
Ultimate Tensile MD	6756
Ultimate Tensile TD	3338
Elongation MD	537
Elongation TD	781
Tear Resistance MD	250
Tear Resistance TD	450
Puncture Resistance	128 gms
Ultimate Prestrech	220–250%
Cling	> / = 50

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE | Bldg 400, Suite 1700 | Atlanta, GA 30328 | USA

© 2019 TUFFflex and the TUFFflex logo are trademarks of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF: 192922

8/19
PKTFSpStretchTDS