

MK600 Hand Length

Performance Paper Masking Tape

DESCRIPTION

A beige, semi-bleached crepe paper coated with a pressure-sensitive natural / synthetic rubber adhesive. Conformable and flexible. A porch industry leader.

PRODUCT APPLICATION

Designed primarily for general purpose bundling, protecting, and various industrial applications, interior paint masking, silk screening, mail rooms, golf club shaft (build-up), carpet pad / pad splicing, freezer tape, and for light bundling, packaging, splicing and tabbing.

GOVERNMENT COMPLIANCE

ASTM D6123 / 6123M, Type I
C.I.D. A-A-883B, Type I

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

BACKING	Crepe Paper
ADHESIVE	Natural/Synthetic Rubber
ADHESION TO STEEL (oz/in of width) PSTC-101	40 (10.9 N/25mm)
TENSILE STRENGTH (lbs/in of width) PSTC-131	21 (92 N/25mm)
ELONGATION (% at break) PSTC-131	7
TOTAL THICKNESS PSTC-133	6.0 (0.15mm)
QUICK STICK TO STEEL (oz/in of width) PSTC-5	18 (4.9 N/25mm)
OPERATING TEMPERATURE RESISTANCE	+50°F ~ +180°F (+10°C ~ +82°C)
COLOR	Beige

TUFFflex™

tufflexpackaging.com
1000 Abernathy Road, N.E. Suite 1700
Atlanta, GA 30328 | USA

© 2015 TUFFflex is a trademark of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.