

WA560 Natural Machine Length

Performance Paper WAT

DESCRIPTION

Natural kraft carton sealing tape manufactured with standard water-activated adhesive.

PRODUCT APPLICATION

Recommended for inner carton sealing or for lightweight cartons that will be shipped in unitized loads or full pallets.

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

PAPER	57 lb (93 g/m ²) Natural Kraft Paper
WATER-ACTIVATED ADHESIVE	15 lb (24 g/m ²) Waxy Maize Starch Based Adhesive, Designated as #410
TOTAL BASIS WEIGHT	72 lb (117 g/m ²)

PHYSICAL PROPERTIES:

CALIPER	5.6 mils (0.14mm)
MD TENSILE	45 lbs/in (197 N/25mm)
CD TENSILE	23 lbs/in (101 N/25mm)

ADHESION (WATER AT RECOMMENDED 110°F/43°C)

FIPAGO	2/0	23
	2/1	42
	5/0	48
	15/0	82

MCLAURIN	34
-----------------	----

TUFFflex™

tufflexpackaging.com
1000 Abernathy Road, N.E. Suite 1700
Atlanta, GA 30328 | USA

© 2015 TUFFflex is a trademark of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.