

WA630 Natural Machine Length

Premium Reinforced WAT

DESCRIPTION

3-way fiberglass reinforced natural kraft carton sealing tape, manufactured with water-activated adhesive.

PRODUCT APPLICATION

Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads. Recommended for use on light weight to average cartons up to 30 pounds.

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

TOP PLY	23 lb Natural Kraft Paper (virgin fibers)
BOTTOM PLY	23 lb Natural Kraft Paper (virgin fibers)
LAMINATING ADHESIVE	14.0 lb High Melt Index Polypropylene Based Co-Polymer
REMOISTENABLE ADHESIVE	15 lb Chemically Grafted Starch Based Copolymer Adhesive, Designated as S3911
MD REINFORCEMENT	2.82 lb (1-1-1-1) 75 Fiberglass (per 72mm), 1/2" spacing
CD REINFORCEMENT	1.34 lb (1-1-1) 150 Fiberglass, 1.20" spacing, 37 degree angle
TOTAL BASIS WEIGHT	79.2 lb

PHYSICAL PROPERTIES:

CALIPER (mils)	6.3
MD TENSILE (lbs/in)	74
CD TENSILE (lbs/in)	26

ADHESION (WATER AT RECOMMENDED 110°F/43°C)

FIPAGO	2/0	49
	2/1	71
	5/0	75
	15/0	90
	MCLAURIN	86

TUFFflex™

tufflexpackaging.com
1000 Abernathy Road, N.E. Suite 1700
Atlanta, GA 30328 | USA

© 2015 TUFFflex is a trademark of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.