

# WA750 Natural Machine Length

## Ultra Reinforced WAT

### DESCRIPTION

3-way fiberglass reinforced, strippable natural kraft carton sealing tape manufactured with water-activated adhesive.

### PRODUCT APPLICATION

Used for two-strip sealing cartons top and bottom. Works well on recycled cartons and non-unitized loads. Recommended using on average to heavyweight cartons up to 65 pounds.

### CONSTRUCTION PER 3,000 SQUARE FEET (metric)

TOP PLY	25 lb Natural Kraft Paper (virgin fibers)
BOTTOM PLY	30 lb Natural Kraft Paper (virgin fibers)
LAMINATING ADHESIVE	15.5 lb High Melt Index Polypropylene Based Co-Polymer
REMOISTENABLE ADHESIVE	16 lb Chemically Grafted Starch Based Copolymer Adhesive, Designated as S3911
MD REINFORCEMENT	5.33 lb (2-2-1-1-2-2), 75 Fiberglass (per 3"), 1/2" spacing
CD REINFORCEMENT	2.91 lb (1-1-1), 150 Fiberglass, 0.55" spacing, 43° angle
TOTAL BASIS WEIGHT	94.7 lb

### PHYSICAL PROPERTIES:

CALIPER (mils)	7.5
MD TENSILE (lbs/in)	89
CD TENSILE (lbs/in)	32

### ADHESION (WATER AT RECOMMENDED 110°F/43°C)

FIPAGO	2/0	38
	2/1	58
	5/0	69
	15/0	87
	MCLAURIN	86

# TUFFflex™

tufflexpackaging.com  
1000 Abernathy Road, N.E. Suite 1700  
Atlanta, GA 30328 | USA

© 2015 TUFFflex is a trademark of Veritiv Corporation. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.